

SNO. 640	Gaz Fidelity	
TYPE	PRESSURIZED	
BUILT	2002. 6	
FLAG	PANAMA	
CLASS	B.V.	
QUALIFICATION	IMO TYPE IIPG	
CALL. SIGN	HOFK	
TEL NO.	773 235 992	
FAX NO.	783 209 338	
DATA NO.		
E-MAIL ADDRESS	master.gazfidelity@amosconnect.com	
TELEX NO.	435 252 510	
DW(MT)	8064.60	
INTERNATIONAL TONNAGE	6502.00	
DOMESTIC TONNAGE	—	
NET TON	2310.00	
LOA (M)	119.97	
BREADTH (M)	19.00	
DEPTH (M)	9.00	
SUMMER DRAFT (M)	6.798	
MAX DRAFT (M)	6.798 M. (WITH VCM=5,592.00 T) DISPLACEMENT 11956.70 MT (8064.6 DWT) IF0=851.0 MT, MDO=67.0MT, F/W=252.0 MT, B/W=878.00 MT	
TANK CAPACITY (CBM)	Total	8,322.979
(NUMBER)	No. 1	2,774.396
	No. 2	2,774.225
	No. 3	2,774.358
MAX. PRESSURE	1.77 Mpa (18.0 KG/CM2)	
MIN. TEMP.	- 0.0 DEG.C	
CARGO SEGREGATION	ONE GRADE	
LOADABLE CARGOES	PROPANE, PROPYLENE I-BUTANE, N-BUTANE P/B MIXTURES, ISOPRENE BUTADIENE, i-BUTYLENE PENTANE, i-PENTENE, VCM NITROGEN GENERATOR	
I.G.PLANT	NITROGEN GENERATOR	
(CAPACITY)	400 m3/hr	
(CONTAINTS)	N2 : 99.9 vol %	
(LOWEST DEWPOINT ACHIEVABL	- 50 C	
CARGO RE-HEATER(TYPE)		
(NUMBER)		
(HEATING MEDIUM)		
(SPEC FOR PROPANE		
FROM - 45 TO 0 C)		
CARGO PUMPS(TYPE)	DEEPWELL	
(CAPACITY-CBM/HR)	300m3/hr per each pump	
(NUMBER)	3(one per each tank)	
CARGO COMPRESSORE (TYPE)	Vertical Single Stage, Water Cooled	
(CAPACITY-CBM/HR)	460 m3/hr	
(NUMBER)	2	
MAIN ENGINE	MAN B&W 6S35MC(Mark7)	
(SERVICE POWER)	4,440 KW	

