

SNO. 639	TAMARA
TYPE	PRESSURIZED
BUILT	37404
FLAG	PANAMA
CLASS	B.V.
QUALIFICATION	IMO TYPE IIPG
CALL. SIGN	HOEH
TEL NO.	335390010
FAX NO.	335390012
DATA NO.	
E-MAIL ADDRESS	master.tamara@amosconnect.com
TELEX NO.	435390010
DW(MT)	6,017.00
INTERNATIONAL TONNAGE	
DOMESTIC TONNAGE	-
NET TON	1,995.00
LOA (M)	117.02
BREADTH (M)	18.23
DEPTH (M)	8.90
SUMMER DRAFT (M)	6.80
MAX DRAFT (M)	6.80M DISPLACEMENT 9,730.74 MT (6,241.74 DWT) IF0=649.2 M3, MDO=129.9 M3, F/W=152.9 M3, B/W=1,405.8 M3
TANK CAPACITY (CBM) - 98%	Total 7,077.059
(NUMBER)	No. 1 3,539.059 No. 2 3,538.139
MAX. PRESSURE	1.77 Mpa (18.0 KG/CM2)
MIN. TEMP.	0 DEG.C
CARGO SEGREGATION	ONE GRADE
LOADABLE CARGOES	PROPANE, PROPYLENE I-BUTANE, N-BUTANE P/B MIXTURES, ISOPRENE BUTADIENE, BUTYLENE PENTANE, PENTENE, VCM
I.G.PLANT (CAPACITY)	NITROGEN GENERATOR 340 m3/hr
(CONTAINTS)	O2 : below 1,000ppm, CO2 : below 5ppm, N2+Ar : 99.9 vol %
(LOWEST DEWPOINT ACHIEVABLE)	- 50 Deg.C
CARGO RE-HEATER(TYPE)	
(NUMBER)	
(HEATING MEDIUM)	
(SPEC FOR PROPANE FROM - 45 TO 0 C)	
CARGO PUMPS(TYPE)	DEEPWELL
(CAPACITY-CBM/HR)	400 M3/Hr
(NUMBER)	2
CARGO COMPRESSORE (TYPE)	OIL-FREE
(CAPACITY-CBM/HR)	467 M4/Hr
(NUMBER)	2
MAIN ENGINE	DIESEL
(SERVICE POWER)	3,900 KW

